

## **TECHNICAL DATA SHEET**

**Econo PVA** 

**PRODUCT CODE: EPVA001** 

COMPILED DATE: 21 JUL 23 REVISE DATE: 21 JUL 25

#### **PRODUCT DISCRIPTION**

Low sheen multi purpose Econo PVA coating

## **INTENDED APPLICATIONS**

Painting of exterior and interior walls

## **PRODUCT FEATURES**

Easy to applicate and clean with no thinning Environmentally friendly with no solvents Low odour

### **TECHNICAL DATA**

**Appearance:** Low sheen, homogeneous emulation

Binder: Styrene Acrylic Co Polymeric

**Colour:** Various see catalogue

**SG:** 1,25 - 1,28

**KU:** 105 - 115 @23Deg C

**pH:** 8,3 - 8,7

**Recommended WFT:** 100 micron

VOC: Low VOC

# **APPLICATION DIRECTIVE**

**Mixing and Thinning:** Single component, stir well before use. Do not dilute.

1 L per 8 square meter, dependant on: Substrate (Profile and porosity) and application

**Coverage:** (with or without geotextile)

**Environment:** 10 to 30 Deg C, Max R Humidity 85%

**Drying time before overcoat:** 3 Hours @23 Deg C, R Humidity 50%

**Substrate:** Cleaned thoroughly, remove old unstable paint.

Treat all areas with primer if applicable.

Substrate must be dry.

### TRANSPORTATION AND STORAGE

**Transport:** Classified as non-hazardous

**Store:** Store away from severe cold, heat and direct sun.

**PACKAGING** 

**Standard:** 1L, 5L, 20L and 1000L

## **SAFETY PRECAUTIONS**

Although the product is non-hazardous, caution should be taken during application and storage. Keep container closed properly and away from children. Avoid contact with eyes, do not ingest. If ingested, drink plenty of water or milk, seek medical attention immediately. Refer to MSDS for complete information.

These recommendations are made as a result of testing and experience, it is believed to be true and in good faith. These directives do not imply any guarantee as the application and surface preparation methods is not within our control.



